

S-26 BUCCANEER LIQUID PLASTICS

S-26 Stabilising Primer

WATER-BASED

General application instructions

S-26 Stabilising Primer is a very unique water based primer designed to adhere to most surfaces such as:

- Face Brick
- Timber
- Asbestos
- Concrete
- Cement
- Plaster
- Create Stone
- Plastic
- Previously painted surfaces
- Old Torch on - Bitumen

It is designed to penetrate the surfaces above. Suitable for exterior and interior use on vertical and horizontal surfaces. One of the world's most versatile primers.

▶ NEVER DILUTE THE PRODUCT!

It can tolerate alkalinity and moisture to a far greater degree than any other conventional alkyd bonding liquid. It will never saponify such as a conventional bonding liquid.

Important: see our Preliminary and General (P&G) Notes

Do not apply Stabilising Primer to wet surface or in rainy weather.

All surfaces must be sound, dry, moisture content below 3%, clean and free from dirt, dust, loose flaking paint and other imperfections that may affect the adhesion.

Stir Stabilising Primer well before using it. It can be used in extreme temperature ranges i.e. +5°C to +30°C and dries normally within minutes. Allow at least 3 to 5 hours before over coating. Over coat within 3 months depending on condition.

Always test the product on a small area before doing an entire surface.

Clean up your application tools with water immediately, use soap if needed.

Use protective gloves and safety glasses when using product.

Keep product containers tightly closed when not in use, in dry and a well ventilated area. Keep product container upright. Keep out of reach of children.

If in any doubts, contact the manufacturer for more details.

Application Tools:	Roller, Brush, Spray Method
Cleaning Tools With:	Water
Spread Rate:	±6m ² per litre depending on substrata
Packaging:	1L, 5L, 20L
Colour:	Milky White but Clear when dry